

inmind

thinking about project



Design your wall with BuzziSkin Printed

Customize your wall with our new BuzziSkin Printed while enhancing your room acoustics at the same time. BuzziSkin Printed is ideal to absorb the high tones in your room.

Are you looking for a sophisticated look that will add a unique feel to your interior?

Go for our Marble Absynth or Marble Emperador print. If you prefer an urban, industrial look we propose our Concrete print or bring nature inside with our two different Green prints or our Jungle print.

Design by Sas Adriaenssens

General

BuzziSkin Printed Concrete, Green 1, Green 2, Jungle, Marble Absynth, Marble Emperador

Front: BuzziSkin Printed Back: Self-adhesive

Roll: 10 m x 0,98 m | 393.70" x 38.58" Thickness: 6 mm + 0,1 mm self-adhesive | 0.24" + 0.04" self-adhesive

 $\vec{\Delta}\vec{|}\Delta$ 1000g/m² | 29.49oz/yd²

> We do not recommend installing BuzziSkin Printed on the ceiling or the floor. BuzziSkin Printed is not suitable as seating surface because it will become fluffy. BuzziSkin Printed can not be applied on vinyl, melamine or any other plasticized surface. No claims concerning deviation in color or thickness will be accepted.

Acoustics

A



Absorption

Content

Configurations	3
Fabrics	4
Dimensions	5
Acoustics	6

Configurations

BuzziSkin Printed

Front: BuzziSkin Printed Back: Self-adhesive

X

Roll: L 10 m W 0,98 m | L 393.70" W 38.58" Thickness: 6 mm + 0.1 mm self-adhesive 0.24" + 0.04" self-adhesive Repeat artwork: Concrete ± 480 cm | 189" Green 1 \pm 250 cm | 98.43" Green 2 \pm 250 cm | 98.43" Jungle \pm 750 cm | 295.28"

Marble Emperador ± 480 cm | 189" Batch to batch variation in repeat artwork length of

± 480 cm | 189"

1-2% may occur.

Marble Absynth

1000g/m² | 29.49oz/yd² \Box

> We do not recommend installing BuzziSkin Printed on the ceiling or the floor.

BuzziSkin Printed is not suitable as seating surface because it will become fluffy.

BuzziSkin Printed can not be applied on vinyl, melamine or any other plasticized surface. No claims concerning deviation in color or thickness will be accepted.



Fabrics

Skin

Composition 100% Recycled P.E.T. Felt + adhesive backing


Weight 1.000 g/m2 | 29.49 oz/yd2 **Abrasion resistance** >7.000 Martindale

Flammability EU: EN 13501.1: 2013 Class C-s2, d0



Dimensions


Length: 10 m | 393.70" Thickness: 6 mm | 0.24"



Acoustics

BuzziSkin Printed

Absorption coefficient



Hz	α^{s}
125	0.02
250	0.01
500	0.07
1000	0.25
2000	0.51
4000	0.66

Absorption Values

 α_{w} 0.15 (ISO 11654)

NRC **0.20** (ASTM - C423)

SAA **0.21** (ASTM-C423)

Glossary

All calculations are based on accredited lab measurements, official document available on Buzzi.Space

Definitions

α	Weighted absorption coefficient	(ISO 11654)
NRC	Noise reduction coefficient	(ASTM - C423)
SAA	Sound absorption average	(ASTM - C423)

Classification of sound absorbers NEN-EN-ISO 11654

- **A** 0.90 | 0.95 | 1.0
- **B** 0.80 | 0.85
- **C** 0.60 | 0.65 | 0.70 | 0.75
- **D** 0.03 | 0.55
- **E** 0.15 | 0.25



inmind